

FEATURES

Supplementary

- Profiles
- QR Code
- Roaming
- Covert Mode
- Radio Check
- Remote Monitor
- Alert Call

Voice Service

- Private Call
- Group Call
- All Call
- PSTN/PABX Call
- Broadcast Call
- Emergency Call
- Call Priority

Analogue Mode

- 2-Tone signalling
- HDC1200

Operating Modes

- Digital Conventional
- Analogue Conventional
- Digital Trunking

Data Services

- Text Message
- Status Message
- Quick Text Message

Connection

- BT Audio
- BT Data
- High Efficiency GNSS
- -GPS
- -GLONASS
- Wide Range of Accessories
- Open API

Safety

- Emergency
- Man Down
- Lone Worker
- Authentication
- Air Interface Encryption
- End-to-End Encryption
- Scrambler
- Disable/Enable
- Micro SD Card

SPECIFICATIONS

General		
Frequency Range	UHF: 350~470MHz VHF: 136~174MHz	
Channel Capacity	1024	
Zone Capacity	64	
Channels per Zone	256	
Channel Spacing	12.5kHz/20kHz/25kHz	
Operating Voltage	7.7V	
Battery(Li-polymer)	2400mAh	
Battery Life (5/5/90)	UHF:26 Hours 22 Hours(GNSS)	VHF:25 Hours 21 Hours(GNSS)
Frequency Stability	±0.5ppm	
Antenna Impedance	50Ω	
Dimensions (H x W x D)	132 x 55 x 29.5mm	
Weight	290g	
Display	0.91 inch OLED Display	
BT	5.0 BLE+EDR	

Receiver	
Sensitivity	Analogue: 0.18μV (12dB SI NAD); 0.16μV (Typical) (12dB SI NAD) Digital: 0.18μV/BER5%
Selectivity	TIA-603: 60dB@12.5kHz / 70dB@20/25kHz ETSI: 60dB@12.5kHz / 70dB@20/25kHz
Inter-Modulation	TIA-603: 70dB@12.5/20/25kHz ETSI: 65dB@12.5/20/25kHz
Spurious Response Rejection	TIA-603: 70dB@12.5/20/25kHz ETSI: 70dB@12.5/20/25kHz
Blocking	TIA-603: 80dB ETSI: 84dB
Hum and Noise	40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz
Rated Audio Power Output	0.5W
Rated Audio Distortion	≤3%
Audio Response	+1 ~ -3dB
Conducted Spurious Emission	<57dBm

Transmitter	
RF Power Output	UHF:1W/4W VHF:1W/5W
FM Modulation	11K0F3E@12.5kHz 14K0F3E@20kHz 16K0F3E@25kHz
4FSK Digital Modulation	12.5kHz Data Only: 7K60FKD 12.5kHz Data and Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm<1GHz; -30dBm>1GHz
Modulation Limiting	±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@25kHz
FM Hum&Noise	40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz
Adjacent Channel Power	60dB@12.5kHz; 70dB@20/25kHz
Audio Response	+1 ~ -3dB
Audio Distortion	≤3%
Digital Vocoder Type	AMBE+2™
Digital Protocol	ETSI-TS102 361-1,-2,-3,-4

Environmental	
Operating Temperature	-30°C~ +60°C
Storage Temperature	-40°C~ +85°C
ESD	IEC 61000-4-2 (Level 4) ±8kV (contact); ±15kV (air)
Dust and Water Protection	IEC60529- IP68
Humidity	Per MIL-STD-810 G Standard
Shock and Vibration	Per MIL-STD-810 G Standard

Location Services	
Accuracy specs are for long-term tracking (95th percentile values>5 satellites visible at a nominal -130dBm signal strength)	
GNSS	GPS, GPS+GLONASS, GPS+BD5
TTFF(Time To First Fix) Cold Start	<1 min (Typical)
TTFF(Time To First Fix) Hot Start	<10 sec (Typical)
Horizontal Accuracy	<5meters

*Radio only - Battery-20°C

ACCESSORIES

Standard



Charger



Adapter(12V/1A)



Battery



Antenna



Belt Clip



Strap

Optional



BT Wireless earpiece



Programming Cable
(USB Port)



BT wireless ring PTT



BT Wireless remote
speaker microphone



Wired Earpiece

APPLICATIONS



Transportation



Manufacturing



Business



Public Safety



Security



Utility



Hytera Communications Europe

939 Yeovil Road, Slough, Berkshire, SL1 4NH

info@hytera-europe.com | www.hytera-europe.com



[www.facebook.com/
HyteraEurope](https://www.facebook.com/HyteraEurope)



[www.instagram.com/
Hytera.Europe](https://www.instagram.com/Hytera.Europe)



[www.linkedin.com/company/
hytera-communications-uk](https://www.linkedin.com/company/hytera-communications-uk)



Subscribe on YouTube

Hytera reserves the right to modify the product design and the specifications. In case of a printing error, Hytera does not accept any liability. All specifications are subject to change without notice.



Professional DMR portable radio HP705

NEXT GENERATION DIGITAL RADIO



NEW TECHNOLOGY, NEW EXPERIENCE, NEW FUTURE

As the leading supplier, Hytera has huge experience in R&D and manufacturing of professional digital radios. Having analyzed and extracted users' need, we perceive that it is not enough to improve the status: the radio needs to be more future ready.

Taking inspiration from the feedback received from our users, we are continuously envisioning and exploring better communication within an ecosystem of new standards, new technologies, new products and new applications across the innovation chain. The HP705 is our brand new professional digital radio, and represents the future on style and functions that refreshes the standards in digital radios, providing more efficient and more reliable communication with loud and clear audio, powerful battery, remarkable portability and ruggedness for ease of use across multiple environments and industries.

HIGHLIGHTS

THINNER AND LIGHTER

An optimized mechanical design and a compact lithium polymer battery are discreetly made to fit into the HP705's design, making the radio only 29.5mm in thickness and 290g in weight. This easy to carry and minimalist design benefits officers by allowing them to keep their focus on the critical mission at hand.

LONGER BATTERY LIFE

HP705 optimizes product design and technologies to reduce power consumption, meanwhile the latest in proven lithium polymer technology is used in the standard battery which is lighter and smaller than ever before.

The new technology achieves a shift life of 26 hours on high transmit power at duty cycle 5/5/90 so ensures a full day of delivering key information and calls.

LOUDER AND CLEARER AUDIO

HP705 equips an optimised powerful loudspeaker that can help users to hear clear sounds even in a noisy environment. Water-porting technology is also used to drain out any water that gets into the speaker cavity, ensuring the audio clarity is maintained in case of water.

AI-based noise cancellation technology can decrease 30dB background noise and howling. No matter what noise environment the calling party is in, it ensures that the called party hears a clear sound.

ENHANCED COVERAGE

The HP705 extends the operational range and improves the talk range through high receiver sensitivity and high transmit power, stretching communications into areas where it simply was not possible before. This enhanced coverage improves the user safety and reduces network cost as much as possible.

HIGHER LEVEL OF RUGGEDNESS

HP705 is designed as per the MIL-STD-810 G. It is IP68 rated, impervious to water jets and submersible to a depth of 2 meters for 4 hours, and also resilient to 2-meter drops onto concrete. No matter where the mission drives the user, the HP705 is the partner to count on, because it can stand up to the toughest environments.

FLEXIBLE WIRELESS CONNECTION

HP705 supports built-in BT 5.0 for wireless connections. The advantage of BT 5.0 is low power consumption, rapid transmission, supports multiple devices and more rich data applications such as BT earpiece, BT Patrol, BT positioning.



0.9-inch colour display



Loud and clear audio



Superior long battery life



AI based noise cancellation



Water-porting design



Global Positioning



BT 5.0 audio and data



Supports Micro SD card